



- NOTE:
1. APPEARANCE AND DIMENSION CHECK.
  2. CONDUCTIVE TEST (SHORT, OPEN WIRE)
  3. DIELECTRIC WITHSTANDING VOLTAGE AC350V.
  4. INSULATION TEST : DC100V, 100MΩ.

7	PULL TAB: W*L=40MM*60MM	3PCS		
6	058A/C40	3PCS	STARCONN	
5	H-S-T: φ12MM*25MM, BLACK	2PCS	SUMITOMO	
4	CABLE: UL20276 AWG30*20P*2 CLEAR WHITE	370MM	EBARA	
3	058C40-4A11A BLACK	1SET	STARCONN	
2	058C40-4G11A GREY	1SET	STARCONN	
1	058C40-4S10A BLUE	1SET	STARCONN	
NO.	PARTS NAME AND DESCRIPTION	Q'TY	MAKER	REMARK

NOTE: 1."G" MEANS GROUND.  
 2. PIN 20 OF C2&C3 IS KEYPIN, PIN 28 OF C2 IS REMOVED, PIN 34 OF C1 IS CUT.

				DESIGNED				RED WING ELECTRONICS CO., LTD				
				DRAWN								
				CHECKED								
A		THE FIRST REVISION		APPROVAL				PART NO.	ULTRA ATA133(391)			
REV.	MARK	CHANGED ITEM	APPR.	DATE	SCALE	FREE	UNIT	MM	CUS.NO.	CWF-133F-F30F7		