



NOTE:
 1. APPEARANCE AND DIMENSION CHECK.
 2. CONDUCTIVE TEST (SHORT, OPEN WIRE)
 3. DIELECTRIC WITHSTANDING VOLTAGE AC TEST:
 4. INSULATION TEST : DC100V, 100MΩ.

9	ACETATE TAPE W*L: 5MM*220MM	3PCS		
8	ACETATE TAPE W*L: 5MM*160MM	1PC		
7	PULL TAB: W*L=40MM*70MM	3PCS	TC&C	
6	058A/C40	3PCS	STARCONN	
5	H-S-T: φ12MM*25MM, BLACK	4PCS	SUMITOMO	
4	CABLE: UL-VSVC AWG30*20P*2(UL20276) CLEAR WHITE	810MM	EBARA	
3	058C40-4A11A BLACK	1SET	STARCONN	
2	058C40-4G11A GREY	1SET	STARCONN	
1	058C40-4S10A BLUE	1SET	STARCONN	
PARTS NAME AND DESCRIPTION		Q'TY	MAKER	REMARK

NOTE: 1. "G" MEANS GROUND.

2. PIN 20 OF C2&C3 IS KEYPIN, PIN 28 OF C2 IS REMOVED, PIN 34 OF C1 IS CUT.

DESIGNED				RED WING ELECTRONICS CO., LTD						
DRAWN										
CHECKED										
A	THE FIRST REVISION		APPROVAL			PART NO.	ULTRA ATA133(394)			
REV.	MARK	CHANGED ITEM	APPR.	DATE	SCALE	FREE	UNIT	MM	CUS.NO.	CWF-133F-F50F20